

PratiKa socket - screw - angled - 32A - 3P + N + E - 380...415 V AC - wall

PKF32W435

Main

Range	Mureva
Product or component type	Socket
Device short name	Mureva socket
Plug, socket category	Low voltage
Poles description	3P + N + E
Network type	AC
Outlet standard	Industrial

Complementary

Mounting mode	Wall-mounted	
Plug, socket, control station shape	Angled	
[In] rated current	32 A	
[Ue] rated operational voltage	380415 V	
Network frequency	50/60 Hz	
Ground lug clockwise position	6 h	
Plug, socket material	Housing: self-extinguishing engineering polymer	
Contacts material	Sleeves: brass	
Connections - terminals	Captive screws	
Cable cross section	2.510 mm²	
Cable outer diameter	21 mm	
Thread type	M25	
Net weight	0.33 kg	
Height	120 mm	
Width	90 mm	
Depth	125 mm	
Colour	Grey (RAL 7035)	
Voltage colour	Red	

Environment

Standards	IEC 60309-2 IEC 60309-1
IP degree of protection	IP44 conforming to IEC 60529

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

IK degree of protection	IK08 conforming to EN 62262 750 °C conforming to IEC 60695-2-1	
Fire resistance		
Relative humidity	50 % at 40 °C	
	70 % at 30 °C	
	90 % at 20 °C	
Ambient air temperature for	35 °C (86400 s)	
operation	-2540 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.000 cm
Package 1 Width	12.500 cm
Package 1 Length	16.000 cm
Package 1 Weight	299.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	18.000 cm
Package 2 Width	27.000 cm
Package 2 Length	27.000 cm
Package 2 Weight	1.955 kg
Unit Type of Package 3	S03
Number of Units in Package 3	12
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	4.314 kg

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	22
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	89350e0d-a4ac-4516-bf86-fdaed8a227fc
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No