

PratiKa wander plug - straight - 32 A - 2P + E - 200...250 V AC - IP67

PKE32M723

Main

Range	Mureva
Product or component type	Wander plug
Device short name	Mureva plug
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

Complementary

Plug, socket, control station shape	Straight
[In] rated current	32 A
[Ue] rated operational voltage	200250 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Sleeves: brass
Connections - terminals	Captive screws
Cable cross section	2.510 mm ²
Cable outer diameter	11.521 mm
cable entry	Cable gland Fair lead
Thread type	Pg 21
Net weight	0.23 kg
Height	152 mm
Width	95 mm
Depth	95 mm
Colour	Grey (RAL 7035)
Voltage colour	Blue

Environment

01	150 00000 0	
Standards	IEC 60309-2	
	IEC 60200 1	
	IEC 00309-1	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

IP degree of protection	IP67 conforming to IEC 60529	
IK degree of protection	IK08 conforming to EN 62262	
Fire resistance	850 °C conforming to IEC 60695-2-11	
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C	
Operating altitude	2000 m	
Ambient air temperature for operation	35 °C (86400 s) -2540 °C	

Packing Units

PCE
1
17 cm
9.4 cm
8 cm
244 g
BB1
6
17.6 cm
26.4 cm
26.8 cm
1.644 kg
S03
12
30 cm
30 cm
40 cm
3.775 kg

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	12
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	661ec80b-b956-4b0a-92bb-53046f4cfb4c
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins